



# Material Safety Data Sheet

## 1. Product and Company Identification

**Product Code** SS  
**Product Name** BRICKFORM® Satinseal™

**Manufacturer** BRICKFORM  
**Address** 11061 Jersey Blvd.  
**City, State, Zip** Rancho Cucamonga, CA 91730

**Emergency Phone** Chemtrec 800-424-9300  
**Business Phone** 909-484-3399  
**Business Fax** 909-484-3318

**Last Updated** July 6, 2005

## 2. Composition / Information on Ingredients

Chemical Name	CAS No.	ACGIH TLV	OSHA PEL	STEL
Acrylic Polymer	Non Hazardous	None Est.	None Est.	None Est.
Dipropylene Glycol Methyl Ether	34590-94-8	None Est.	None Est.	None Est.

## 3. Hazards Identification

**Emergency Overview**  
White viscous liquid with mild odor

**Signs and Symptoms of Exposure**

**Ingestion**  
May cause nausea and vomiting.

**Inhalation**  
N/A

**Eyes**  
Can cause irritation of the eye.

**Skin**  
May cause skin irritation.

**Potential Environmental Hazards**  
N/A

## 4. First Aid Measures

**Ingestion**  
DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. GET MEDICAL ATTENTION IMMEDIATELY.

**Inhalation** N/A

**Eyes**  
DO NOT RUB. Flush eyes with plenty of water for 15 minutes while holding eyelids open. If irritation persists, GET MEDICAL ATTENTION IMMEDIATELY.

**Skin**  
Wash with plenty of soap and water. If rash develops, get medical attention.

# BRICKFORM

## Material Safety Data Sheet

BRICKFORM Satinseal / SS  
Last Updated July 6, 2005

### 5. Fire Fighting Measures

Flash Point N/A  
Autoignition Temperature N/A

Lower Explosive Limit N/A  
Upper Explosive Limit N/A

**Unusual Fire Explosion Hazards**  
N/A

**Extinguishing Media**

Dry Chemical or Carbon Dioxide

**Special Fire Fighting Procedures**

Fire Fighters must wear a self-contained breathing apparatus or air masks. Containers exposed to fire should be kept cool with water spray. A water stream directed into the fire may cause subsequent spread of fire.

### 6. Accidental Release Measures

Keep people away. Ventilate confined spaces. Open all windows and doors. Flush with water to a tank or an open well-ventilated area. Recover by pumping. Keep product out of sewers, watercourses, and soil by dyking or impounding. Absorb with sand, earth, or other suitable absorbent. Control runoff and isolate discharge material for proper waste-disposal method. Use non-leaking containers, seal tightly, and label properly. Dispose of in accordance with applicable local, county, state, and federal regulations.

### 7. Handling and Storage

**Safe Handling and Storage**

CAUTION: Do not store in temperatures below -6.1°C (45°F). Keep from freezing. Keep containers closed. DO NOT WELD, heat or drill on or near containers. Even empty containers can contain vapors or residue.

### 8. Exposure Controls and Personal Protection

**Engineering controls**

Use only with ventilation in confined areas, especially when using spray equipment.

**Personal Protective Equipment**

Use splash goggles to protect eyes. Avoid inhalation and use only MSHA or NIOSH approved atmosphere supplying or air purifying respirators in confined or enclosed spaces for organic vapors, if needed. Use chemical-resistant gloves and avoid prolonged or repeated skin contact.

**Other Protective Clothing Equipment**

An eyewash station and a safety shower should be available.

**General Work Practices Hygiene Considerations**

Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Use good hygiene when handling this product. Cleanse skin thoroughly after handling and before eating or drinking. Product is easily removed with waterless, hand cleaners followed by washing thoroughly with soap and water. Remove contaminated clothing and launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean and dry before reuse.

**Exposure Guidelines**

Please see section 2.

# BRICKFORM

## Material Safety Data Sheet

BRICKFORM Satinseal / SS  
Last Updated July 6, 2005

### 9. Physical and Chemical Properties

<b>Physical State</b> Liquid	<b>Appearance/Color/Odor</b> White Viscous/Mild Odor
<b>Melting Point/Range</b> N/A	<b>Boiling Point/Range</b> >100° C (212° F)
<b>Solubility in Water</b> Soluble	<b>How to Detect this Compound</b> N/A
<b>pH</b> N/A	<b>Specific Gravity (Water = 1)</b> 1.01 - 01.05
<b>Molecular Weight</b> N/A	<b>Freezing Poing</b> 0.0° C (32° F)
<b>Vapor Pressure (mmHg)</b> 24 @ 25° C (77° F)	<b>Vapor Density (Air = 1)</b> 6
<b>VOC</b> <100 grams/liter (3.33 lbs./gallon)	

### 10. Stability and Reactivity

**Stability** Stable  
**Hazardous Polymerization** Will not occur  
**Conditions To Avoid** N/A  
**Materials To Avoid** Water reactive chemicals.  
**Hazardous Decomposition Products** N/A

### 11. Toxicological Information

N/A

### 12. Ecological Information

N/A

### 13. Disposal Considerations

Use non-leaking containers, seal tightly and label properly. Do not incinerate closed containers. Dispose of in accordance with applicable local, county, state, and federal guidelines. Do not dispose in streams, wells, lakes, rivers, oceans, or sewers.

### 14. Transportation Information

**DOT Proper Shipping Name** Paint Related Material  
**DOT Hazard Class ID Number** Non-hazardous. Not required. Class 55.

### 15. Regulatory Information

**Reportable Quantity** N/A

**NFPA Rating** 0=Insignificant, 1=Slight, 2=Moderate, 3=High, 4=Extreme

**Health** 1  
**Flammability** 0  
**Reactivity** 0

# BRICKFORM

## Material Safety Data Sheet

BRICKFORM Satinseal / SS  
Last Updated July 6, 2005

### 15. Regulatory Information...continued

Carcinogenicity Lists	No
NTP	No
IARC Monograph	No
OSHA Regulated	Yes

**STATE WARNING**  
N/A

#### FEDERAL WARNING

Section 313 Supplier Notification: This product contains the following toxic chemical(s) subject to the reporting requirements of SARA TITLE III, Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

N/A

### 16. Other Information

**IMPORTANT!** Read this MSDS before use or disposal of this product. Pass along the information to employees and any other persons who could be exposed to the product to be sure that they are aware of the information before use or other exposure.

This MSDS has been prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200). To the best of our knowledge, the information contained herein is accurate and the information is based on sources believed to be reliable. However, since data, safety standards, and government regulations are subject to change, BRICKFORM makes no warranty, either expressed or implied with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. The data on this sheet is related only to this specific material. It may not be valid for this material if used in combination with any other materials. It is the user's responsibility to determine suitability and completeness of this information with regards to a particular use. Additional information may be necessary or helpful for specific conditions and circumstances of use. Unknown hazards may exist and this material should be used with caution. BRICKFORM assumes no legal responsibility for use or reliance upon this data.