

# K A U F M A N

PRODUCT  
INFORMATION

KAUFMAN  
PRODUCTS  
INC.

3811 CURTIS  
AVENUE

BALTIMORE,  
MARYLAND  
21226-1131

410-354-8600  
800-637-6372  
www.kaufman  
products.net

## KleenLease 28 OTC

### Description

KleenLease 28 OTC is a ready-to-use, chemically active concrete, drying-type form release agent. It is composed of specially blended fatty acids dissolved in an extremely light mineral oil carrier. The fatty acids promote ease of stripping and help to keep the forms clean without killing the concrete surface. It never leaves a whitish powder on the surface of the concrete. The very light carrier provides a non-transferring, frictionless surface to eliminate air voids on the concrete surface. This is especially important to facilitate light applications, so necessary for optimum performance. KleenLease 28 OTC meets all VOC content laws of the Ozone Transport Commission and the Environmental Protection Agency.

### Uses

Provides a clean release every time from either gray or white concrete. It is designed to be used with metal, aluminum, wood or plastic forms or pallets. In fact, use it on any surface coming into contact with concrete. KleenLease 28 OTC produces a dry form surface to avoid coating cables and for additional safety to the workers.

Excels with architectural concrete wall forms, site cast columns, bridge decks, shear keys, pre-stressed beams, and high pressure pipe.

### Specifications

CE 204, Section 7.10  
CE 204, Section 17.4

### Packaging

275 gallon tote (1,040.88 Liters)  
55 gallon drum (208.15 Liters)  
5 gallon drum (18.93 Liters)

### VOC

245 grams/liter  
Meets applicable standards

### Directions

#### Application

Use as the product is furnished. Do not dilute. Form surfaces should be clean, dry and free of contaminants. Apply KleenLease 28 OTC by spray. Wipe off any excess material that may have accumulated in the lower sections or indentations of the form. If spraying, use 40 psi or more. Flat spray tips are recommended.

### Coverage Rates

Hard, smooth surfaces - up to 3000 sq. ft./gal.  
Pre-treated plywood - up to 1500 sq. ft./gal.  
Untreated plywood - approximately 900 sq. ft./gal.

### Precautions

Prolonged storage, especially at temperatures below 40°F may cause separation. Warming the above 40°F and agitation will restore the product to its original condition. When used during cold weather, stir before each use. Too much release agent may cause small surface holes, discoloration, soft spots, concrete build-up and increased difficulty in stripping. Some synthetic form surfaces are degraded when used with KleenLease 28 OTC. Do not dilute with other products. Test before use on white concrete to be sure results are satisfactory. Read Material Safety Data before using.

F:\T\Eng. Literature w-out Heading\029.doc Mar-05

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.