



Material Safety Data Sheet

1. Product and Company Identification

Product Code RA
Product Name BRICKFORM® Antique Release™

Manufacturer BRICKFORM
Address 11061 Jersey Blvd.
City, State, Zip Rancho Cucamonga, CA 91730

Emergency Phone Chemtrec 800-424-9300
Business Phone 909-484-3399
Business Fax 909-484-3318

Last Updated July 6, 2005

2. Composition / Information on Ingredients

Chemical Name	CAS No.	ACGIH TLV	OSHA PEL	STEL
Nuisance Dusts	Mixture	10mg/m ³	5mg/m ³	N/A

3. Hazards Identification

Emergency Overview

Colored, sandy powder. Overexposure to dust can cause chronic lung injury. Acute silicosis may develop in a short time with heavy exposure. Silicosis can be progressive and may cause death.

Signs and Symptoms of Exposure

Ingestion

May cause discomfort if swallowed.

Inhalation

Avoid inhalation. Prolonged exposure to dust may result in irritation to upper respiratory tract. Chronic lung injury can occur.

Eyes

May cause irritation, inflammation or abrasion.

Skin

Prolonged and repeated contact can cause abrading of the skin or defatting drying of the skin, which may result in skin irritation and dermatitis.

Potential Environmental Hazards

N/A

4. First Aid Measures

Ingestion

Should not cause any significant health problem. If a large amount is ingested, drink large quantities of water and induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY.

Inhalation

Remove victim to fresh air. If respiratory symptoms persist or develop, GET MEDICAL ATTENTION. DO NOT RUB. Flush eyes with plenty of water for 15 minutes while holding eyelids open. If irritation persists, GET MEDICAL ATTENTION IMMEDIATELY.

BRICKFORM

Material Safety Data Sheet

BRICKFORM Antique Release / RA
Last Updated July 6, 2005

4. First Aid Measures...continued

Eyes

DO NOT RUB. Flush eyes with plenty of water for 15 minutes while holding eyelids open. If irritation persists, GET MEDICAL ATTENTION IMMEDIATELY.

Skin

Wash with soap and water. Remove contaminated clothing and shoes. Do not reuse until cleaned. If persistent irritation occurs, GET MEDICAL ATTENTION.

5. Fire Fighting Measures

Flash Point N/A

Lower Explosive Limit N/A

Autoignition Temperature N/A

Upper Explosive Limit N/A

Unusual Fire Explosion Hazards

N/A

Extinguishing Media

Product is not flammable. Use standard fire-fighting procedures without regard to product.

Special Fire Fighting Procedures

Firefighters should use a self-contained breathing apparatus.

6. Accidental Release Measures

Shut off and eliminate all ignition sources. Keep people away. Vacuum, scoop, or broom-up spilled powders and place in containers. Avoid generation, exposure, and inhalation of dust. Collect spilled powders, place in non-leaking containers, seal tightly, and label properly. Dispose of in accordance with applicable local, county, state, and federal regulations.

7. Handling and Storage

Safe Handling and Storage

Store in a cool, dry place, away from acids and strong oxidants. Keep containers closed.

8. Exposure Controls and Personal Protection

Engineering controls

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup to dust in air.

Personal Protective Equipment

All personnel must wear OSHA-NIOSH approved dust respirators when working with or near this product. Please refer to OSHA standards in 29 CFR 1910.134. Wear safety goggles to protect eyes. Aprons and gloves should be worn to minimize contact with skin.

Other Protective Clothing Equipment

An eyewash station should be available.

General Work Practices Hygiene Considerations

Minimize breathing of dust. Avoid prolonged or repeated contact with skin. Use good hygiene when handling this product. Cleanse skin thoroughly after handling and before eating or drinking. Product is easily removed with waterless, hand cleaners followed by washing thoroughly with soap and water. Remove contaminated clothing and launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean and dry before reuse.

Exposure Guidelines

Please see section 2.

BRICKFORM

Material Safety Data Sheet

BRICKFORM Antique Release / RA
Last Updated July 6, 2005

9. Physical and Chemical Properties

Physical State Powder
Melting Point/Range N/A
Solubility in Water Negligible
pH N/A
Molecular Weight N/A
Vapor Pressure (mmHg) N/A
VOC N/A

Appearance/Color/Odor Various colors/N/A
Boiling Point Range N/A
How to Detect this Compound N/A
Specific Gravity Approximately 3
Percent Volatiles N/A
Vapor Density (Air=1) N/A

10. Stability and Reactivity

Stability Stable
Hazardous Polymerization Will not occur
Conditions To Avoid N/A
Materials To Avoid Organic and inorganic acids.
Hazardous Decomposition Products Reacts with acid to form carbon dioxide gas.

11. Toxicological Information

N/A

12. Ecological Information

N/A

13. Disposal Considerations

Use non-leaking containers, seal tightly and label properly. Dispose of in accordance with applicable local, county, state, and federal guidelines. Do not dispose in streams, wells, lakes, rivers, oceans, or sewers.

14. Transportation Information

DOT Proper Shipping Name Dry Cement Color
DOT Hazard Class ID Number Non-hazardous. Not required. Class 55.

15. Regulatory Information

Reportable Quantity N/A

NFPA Rating 0=Insignificant, 1=Slight, 2=Moderate, 3=High, 4=Extreme

Health 2
Flammability 0
Reactivity 0

BRICKFORM

Material Safety Data Sheet

BRICKFORM Antique Release / RA
Last Updated July 6, 2005

15. Regulatory Information...continued

Carcinogenicity Lists	No
NTP	No
IARC Monograph	No
OSHA Regulated	No

STATE WARNING

N/A

FEDERAL WARNING

Section 313 Supplier Notification: This product contains the following toxic chemical(s) subject to the reporting requirements of SARA TITLE III, Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

N/A

16. Other Information

IMPORTANT! Read this MSDS before use or disposal of this product. Pass along the information to employees and any other persons who could be exposed to the product to be sure that they are aware of the information before use or other exposure.

This MSDS has been prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200). To the best of our knowledge, the information contained herein is accurate and the information is based on sources believed to be reliable. However, since data, safety standards, and government regulations are subject to change, BRICKFORM makes no warranty, either expressed or implied with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. The data on this sheet is related only to this specific material. It may not be valid for this material if used in combination with any other materials. It is the user's responsibility to determine suitability and completeness of this information with regards to a particular use. Additional information may be necessary or helpful for specific conditions and circumstances of use. Unknown hazards may exist and this material should be used with caution. BRICKFORM assumes no legal responsibility for use or reliance upon this data.